Not Your Uncle's Old Mobe . . . But Maybe Your New One? News from the Factory Floor

The High Performance Manufactured Home

Component	NEEM (Base)	НРМН			
Ceiling	R-40	R-45 (insulated to R-49 target)			
Floor	R-33	R-38 (U=0.028 as per NEEM specs.)			
Wall	R-21	R-26 (R-21 plus R-5 foam sheathing)			
Window	U=0.35	U=0.22			
Door	R-5	R-5			
Duct Leakage	6% of Supply	No ducts			
Target U _o	0.054	0.040			
Heating System	Electric Forced Air Furnace	DHP/ Elec. Res. Hybrid Zonal			
Lighting	1.4 W/ft ²	0.7 W/ft ² (most all is CFL or LED)			
Infiltration	0.25 ACH (natural)	0.25 ACH (natural)			
Ventilation Whole House Fan, 32 W continuous (0.1 ACH added)		Whole House Fan, 32 W continuous (0.1 ACH added)			
DHW (EF)	EF =0.93	EF=2.0 Heat Pump Water Heater			
Appliances and Misc.	Standard refrigerator, Energy Star dishwasher	Energy Star refrigerator and dishwasher / Low-flow showerheads and faucet aerators			

1st Four Prototype HPMHs







No Ducts=Fully Insulated Floor



Stuffed Full




Walls With R-5 Foam Sheathing



Well-Flashed U-.22 Windows



R-49 Attic With Attention to Eaves



Dual-Vented HPWH De-coupled from Home Interior—Draws from Crawlspace



DHP Hybrid Zonal Space Conditioning



DHP Hybrid Zonal Space Conditioning











The Secondary Heating Component




The "Hybrid-Zonal" Approach



Measuring the Results



How's it Working? SEEM predicts . . .




HPMH #1 Monthly Usage



1st 7 months = 5,700 kWh ~ 9,800 kWh annual use

Is it Comfortable?


Room Temperatures with a Single DHP Providing over 95 Percent of the Heating During Typical Western Washington or Oregon Winter Weather



How is the Heating System Being Used?

Outdoor	Ave Watts/ Deg.	Ave DHP Pwr	Ave Zone Heat	Ave Zone Heat	Ave Zone Heat	Ave Indoor		Total Heating	
Temp	(F) Delta-T	(W)	Bdrm 2(W)	Mstr Bdrm (W)	Mstr Bath (W)	Temp (F)	No. Hours	kWh	ER kWh
18	38	1660	0	0	0	65.0	1.2	2.0	0.0
19	35	1529	0	0	0	65.1	1.6	2.4	0.0
20	25	1036	0	48	0	65.2	3.1	3.4	0.2
21	27	1071	0	56	0	65.3	3.1	3.5	0.2
22	28	1088	0	56	0	64.9	3.6	4.1	0.2
23	30	1057	0	74	1	64.4	6.4	7.3	0.5
24	33	1312	0	5	2	64.8	14.7	19.3	0.1
25	30	1113	0	0	3	64.4	4.2	4.7	0.0
26	29	1037	0	0	8	64.5	4.4	4.5	0.0
27	27	967	0	0	0	65.5	5.1	4.9	0.0
28	31	1109	0	0	0	65.7	9.2	10.2	0.0
29	31	1066	2	12	0	65.9	11.3	12.2	0.2
30	31	1055	0	19	2	66.3	32.7	35.1	0.7
32	34	901	0	130	16	66.0	19.4	20.3	2.8
33	37	960	0	107	62	66.1	31.2	35.2	5.3
34	33	915	0	33	55	66.6	27.1	27.1	2.4
35	28	796	0	7	30	66.8	13.3	11.1	0.5
36	28	768	0	0	21	66.8	7.6	6.0	0.2
37	31	754	0	0	100	66.8	4.7	4.0	0.5
38	33	816	0	0	37	66.6	14.9	12.7	0.6
39	31	769	0	0	4	66.9	9.9	7.6	0.0
40	30	767	0	0	13	67.4	20.9	16.3	0.3
41	32	783	0	0	13	67.4	12.6	10.0	0.2
42	28	702	0	0	2	68.4	17.8	12.5	0.0
43	30	715	0	0	2	68.0	12.3	8.8	0.0
44	32	699	0	0	0	67.6	8.4	5.9	0.0
45	31	661	0	0	11	68.0	9.8	6.6	0.1
46	36	657	0	0	84	67.8	7.6	5.7	0.6
47	30	616	0	0	0	67.9	5.1	3.1	0.0
48	30	582	0	0	0	67.4	5.5	3.2	0.0
49	30	563	0	0	0	67.7	2.1	1.2	0.0
50	30	535	0	0	0	68.0	1.9	1.0	0.0
51	31	519	0	0	0	68.1	1.3	0.6	0.0
Grand Total	32	891	0	26	20	66.6	333.8	312.8	15.4

Room for Improvement?



Can I Buy One? The Path to Market

- Hard costs are running \$11k to \$14k per home to upgrade from Energy Star
- Assuming some level of savings from establishing purchase contracts, retail probably will be a \$20k+ price adder
- Opportunities for value engineering yet to be tested—window trade-off, different wall assemblies, newly arriving HPWH equipment?